



S.N.	Description	Aagaman Cement Primer for Exterior is formulated from Acrylic Co-Polymer. That is high opacity, low-odour, water-based chalky matt hard primer for walls, ceilings and fine plaster work. The resultant soft, deep matt finish is ideally suited for priming to bed-rooms, living-rooms, dining areas and other low- traffic areas.
	Application	It is an ideal for Exterior walls priming ,e.g concrete ,masonry , brick , etc.
	Technical Data	Product Type : Aagaman Exterior Cement Primer
		Appearance : Viscous liquid in white colour
		Film Type : Matt , smooth no , free from lump , foam and thixotropic
		pH : 8 - 10
		Density / Specific Gravity : 1.48- 1.50
		Solid Content : More than 60 %
		Viscosity : 140 Sec in Fc 4
		Application : By Brush , Roller or Spray
		Dilution : 2 : 1 by Vol/Vol
		Drying Time : Within 1 Hour
		Gloss Level : Matt (Less 5 %)
		Theoretical Coverage : 100-120 Sq.ft /ltr/coat
		Recommendation film thickness : 20 Microns dry, per coat
		Recommended number of coats : 2
		Time to recoat : 4 hours min
		Volume Solid : 28 %
		Colour availability : Non Applicable
	Packing Size	20 Ltr, 10 Ltr , 4 Ltr , & 1 Ltr
	Shade	Not Applicable
	Approvals & Standards	Water Vapour permeability (BS EN ISO 7783) mean Sd < 0.03m , mean V : > 680 gm/m ² /day Water Vapour Permeability Classification (EN 1062 -1) , Class VI (high) Manufactured under the auspices of ISO 9001 : 2015 Quality & ISO 14001 ; 2015 environmental management systems 2004/42/EC EU limit value for this product (catA/a WB) :30g/l (2010). This product contains max 2gm/l VOC This product has been tested under the regulation outlined in French Indore Air quality Deree No 2011 – 321 – Arrete April 2011 and awarded on A +
	Application Instruction	Surface Preparation : New Surface : Leave the surface at least 1 month to completely cured and dried Substance must be free from dust ,dirt ,grease or loose particles Old Surface: The surface should be clean and dry. If fungus or mildew growth must be cleaned off before coating Primer : New Surface : priming by alkali resistance Aagaman Exterior Primer 1 coat Old Surface : Priming by proper Primer Coating System: Apply Tata Acrylic Distemper (White Base), Interior Emulsion paint for interior to top -coat 2-3 coats. Drying time to recoat 2 -3 hours by approximately
	Coverage	16 sq mt / gallon /coat
	Storage and Shelf Life	Maximum 1 years in sealed container. Protect from sunlight . Keep container tightly closed when not in use and again after correct storage. Keep it in well - ventilated place .



	Safety , Health and Environment information	<ul style="list-style-type: none">● Keep out of reach of children● Use in a well ventilated area● Avoid contact with skin or eyes● If on skin , wash with plenty of soap and rinse skin with clean water● Do not use empty container for food stuff● Avoid release to the environment
	Area for use Primer	Any Cementous , masonry areas for priming or old surface or new surface use Tata Wall Putty before apply it on damp free area