



Sl no	Description	Tata Altee Exterior Emulsion Paint for exterior is formulated from Acrylic Polymer. That is a choice for Premium Exterior Emulsion paint. It provides smooth and beautiful finish. Good protection against fungus .It has smooth and Sheen based Emulsion Paint as easily washable and good durability and scrub resistivity
Application	It is an ideal for interior walls decoration ,e.g concrete ,masonry , brick , etc	
Technical Data	Product Type : Pure Acrylic Co polymer	
	Appearance : Viscous liquid in white colour	
	Film Type : Slight Sheen with excellent durability,brushability and scrub resistivity	
	pH : 8 - 10	
	Density / Specific Gravity : 1.20 – 1.25	
	Solid Content : Not Applicable	
	Viscosity : 100 Sec in Fc 4	
	Application : By Brush , Roller or Spray	
	Dilution : 2 : 1 by Vol/Vol	
	Drying Time : Within 1 Hour	
Application Instruction	Surface Preparation : New Surface : Leave the surface at least 1 month to completely cured and dried Substance must be free from dust ,dirt ,grease or loose particles Old Surface : The surface should be clean and dry. If fungus or mildew growth must be cleaned off before coating Primer : New Surface:priming by alkali resistance Tata Toyota Exterior Primer 1 coat Old Surface : Priming by proper Primer Coating System : Apply Lukol Interior Royal Emulsion paint for interior to top -coat 2-3 coats. Drying time to recoat 2 -3 hours by approximately	
Coverage	120-140sq.ft./letre /coat	
Storage and Shelf Life	Maximum 3 years in sealed container. Protect from sunlight . Keep container tightly closed when not in use and again after correct storage. Keep it in well - ventilated place .	
Safety , Health and Enviornment information	<ul style="list-style-type: none"><li>Keep out of reach of children</li><li>Use in a well ventilated area</li><li>Avoid contact with skin or eyes</li><li>If on skin , wash with plenty of soap and rinse skin with clean water</li><li>Do not use empty container for food stuff</li><li>Avoid release to the environment</li></ul>	
Packing	20 Ltr , 10 Ltr , 4 Ltr& 1 Ltr	