Head Office: Bharatpur, Chitwan web: www.tatapaints.com.np Tel.: 9855058987, 9855052281

TECHNICAL DATA SHEET OF TATA ANMOL PREMIUM INTERIOR EMULSION PSAINT

SI	Description	Tata Anmol Interior Premium Emulsion Paint for Interior is formulated from
no		Acrylic Polymer.That is a choice for Premium Interior Emulsion paint. It
		provides smooth and beautiful finish. Good protection against fungus .lt has
		smooth and Sheen based Emulsion Paint as easily washable
	Application	It is an ideal for interior walls decoration ,e.g concrete ,masonry , brick , etc
	Technical Data	Product Type : Pure Acrylic Co polymer
		Appearance : Viscous liquid in white colour
		Film Type : Slight Sheen with excellent durability, brushbility and
		scrub resistivity
		pH : 8 - 10
		Density / Specific Gravity : 1.20 – 1.25
		Solid Content : Not Applicable
		Viscosity : 100 Sec in Fc ₄
		Application : By Brush , Roller or Spray
		Dilution : 2 : 1 by Vol/Vol
		Drying Time : Within 1 Hour
	Application	Surface Preparation: New Surface: Leave the surface at least 1 month to
	Instruction	completely cured and dried Substance must be free from dust ,dirt ,grease or
		loose particles
		Old Surface: The surface should be clean and dry. If fungus or mildew growth
		must be cleaned off before coating
		Primer: New Surface:priming by alkali resistance Aagaman Interior Primer 1 coat
		Old Surface : Priming by proper Primer
		Coating System : Apply Lukol Interior Royal Emulsion paint for interior to
		top -coat 2-3 coats. Drying time to recoat 2 -3 hours by approximately
	Coverage	100-110sq.ft/letre/coat
	Storage and Shelf	Maximum 3 years in sealed container. Protect from sunlight . Keep container
	Life	tightly closed when not in use and again after correct storage. Keep it in well
	Life	- ventilated place .
	Safety , Health and	Keep out of reach of children
	Enviornment	Use in a well ventilated area
	information	Avoid contact with skin or eyes
		• If on skin , wash with plenty of soap and rinse skin with clean water
		Do not use empty container for food stuff
		Avoid release to the environment
	Packing	20 Ltr , 10 Ltr , 4 Ltr& 1 Ltr
		Į.